

EC-CERTIFICATE OF CONSTANCY OF PERFORMANCE

569/2131/CPR/2017

of the product:

N2 SAFETY BARRIER FOR SIDE EDGE

MODEL: BLIDN2R4

placed on the market by:

INDUSTRIAS DUERO S.L.

González Dávila,1 - 28031 Madrid – España

PERFORMANCE UNDER IMPACT:

a) Containment Level	N2
b) Severity Impact	A
c) Normalised Working Width	W4 (1.2 m)
d) Normalised Dynamic Deflection	1.1 m

DRAWING: A1-00449

INSTALLATION MANUAL: BLIDN2R4

TEST REPORT: CIDAUT E12-0079 (TB11)

AISICO N° 1447 (TB32)

of 2016/10/27

of 2016/11/02

of 2016/01/18

of 2016/11/09

DURABILITY: GALVANISED STEEL IN ACCORDANCE WITH EN ISO 1461

RESISTANCE TO SNOW REMOVAL: NPD

DANGEROUS SUBSTANCE: NPD

CONDITIONS FOR USE: CONFORMITY WITH I.T.T. CONFIGURATION

enabled production plants:

INDUSTRIAS DUERO S.L.

González Dávila,1 - 28031 Madrid - Spain

Cornarques Pais Valencia km 343 - 46930 Quart de Poblet –
Valencia - Spain

determined by initial type-testing (I.T.T.); The Producer shall implement the Factory Production Control (FPC) which guarantees compliance with type examined and with the requirements of the Harmonized Standard conforming to System Procedure 1 – Annex V of Regulation 305/2011 (EU). This certificate attests to the application and compliance with the requirements of Annex ZA of the standard:

EN 1317-5:2007+A2:2012/AC:2012

permits the Manufacturer to place on the product the CE marking followed by the identifying of the Notified Body “2131”.

The validity of this Certificate is subject to the regularity of the Surveillance on its FPC.

Any damage caused by product defects remains the responsibility of the Producer (85/347/ECC).

Issue date: 2017/01/12

This certificate consists of this page and Annex 1

Chairman

(Ing. Stefano Calamanti)



ANNEX 1

TO THE CERTIFICATE OF PERFORMANCE

569/2131/CPR/2017

of the product:

N2 SAFETY BARRIER FOR SIDE EDGE**MODEL: BLIDN2R4**

placed on the market by:

INDUSTRIAS DUERO S.L.**González Dávila,1 - 28031 Madrid – España****MODIFICATION: M1**
Approved on 2017/01/11**Model:BLIDN2R4****Description of modification:** utilization Beam with 3 longitudinal holes**Drawing:** C3-00297 of 2012/07/27**Installation Manual:** BLIDN2R4 of 2016/11/02**Technical documentation:** Validation INDUSTRIAS DUERO del 25/09/2012**Issue date:** 2017/01/12**Chairman**
(Ing. Stefano Calamini)
