

Certificate of constancy of performance

(Reg.-Nr. 1794-CPR-11.110.23-1317-5)

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Road restraint systems – Safety barriers

placed on the market by

Licensor:
DELTABLOC Int. GmbH
Kirchdorfer Platz 2
2752 Wöllersdorf
Austria

Producer / Placed onto the market by
DELTABLOC Sverige AB
Florettgatan 14
254 67 Helsingborg
Sweden

and produced in the manufacturing plant

MT-Betong AB
Ulvarydsvägen 4
285 35 Markaryd
Sweden

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1317-5:2007+A2:2012/AC:2012

under system 1 are applied and that the product fulfills all the prescribed requirements set out above.

This certificate was created on 31.03.2023 and remains valid until 16.12.2026.

Munich, 31.03.2023

page 1-3



Dipl.-Phys. H. Zimmermann
Deputy Director of the certification body

Certificate of constancy of performance

(Reg.-Nr. 1794-CPR-11.110.23-1317-5)

Series	Containment level	Normalized Working width	Normalized vehicle intrusion	Impact severity	Normalized dynamic deflection	Resistance class to snow removal	Assessment/ Modification report	Production drawing	Installation drawing	Remarks
DB 80										
DB 80 6m T180S	H2/L2	W5	VI5	B	1,1 m	4	725114855_1	B733085	K733085	free standing
DB 80 6m T180S STM	H2/L2	W5	VI5	B	1,1 m	4	725037644	B668533	K668533	free standing
DB 80E 6m T150S H85	H2	W1	VI1	B	0,1 m	4	60302 Rev. 1	B668688	K668688	5 cm embedded
DB 80E 6m T150S H85 E4	H2	W1	VI2	B	0,0 m	4	725154075	B706749	K738455-DE.2 & -4	4 cm embedded, on asphalt and concrete
DB 80AS-E										
DB 80AS-E 6m T150S H87	H2	W1	VI2	B	0,0 m	4	63864_rev2	B706879	K738236 K706879	7 cm embedded
DB 80AS-E 6m T150S H92	H2	W1	VI2	B	0,0 m	4	63864_rev2	B706985	K738237 K706985	7 + 5 cm embedded
DB 80AS-E 6m T150S H92 BR	H2	W1	VI1	B	0,0 m	4	63864_rev2	B706985	K738238 K714750	backing beam reinforced
DB 80AS-E 6m T150S H92 BU	H2	W2	VI2	B	0,3 m	4	725117424_2	B706985	K738239	backing beam unreinforced
DB 80AS-E 6m T150S H87 BF	H2	W1	VI2	B	0,0 m	4	725117424_3	B706879	K738147	1 row, 7 cm embedded, optionally back filled
DB 80AS-E 6m T150S H92 BR BF	H2	W1	VI1	B	0,0 m	4	725117424_3	B706985	K738161	1 row, backing beam reinforced, optionally back filled
DB 80AS-E 6m T150S H92 BU BF	H2	W2	VI2	B	0,3 m	4	725117424_3	B706985	K738162	1 row, 12 cm embedded, backing beam unreinforced, optionally back filled
DB 80AS-E 6m T150S H92 BF 2R	H2	W5-W8	VI5	B	0,2 m	4	725117424_6_rev2	B706985 B731085	K738145	2 row, back filled, 12 cm embedded
DB 80AS-E 6m T150S H92 BF	H2	W7	VI5	B	0,2 m	4	725117424_6_rev2	B706985	K738163	1 row, back filled, 12 cm embedded

Munich, 31.03.2023

page 2-3




Dipl.-Phys. H. Zimmermann
 Deputy Director of the certification body

Certificate of constancy of performance

(Reg.-Nr. 1794-CPR-11.110.23-1317-5)

Series	Containment level	Normalized Working width	Normalized vehicle intrusion	Impact severity	Normalized dynamic deflection	Resistance class to snow removal	Assessment/ Modification report	Production drawing	Installation drawing	Remarks	
DB 80P											
DB 80P 6m T150S ZDC	H2	W2	VI4	B	0,3 m	4	725149643_2	B733149	K733239	double sided, one sided pinned, on asphalt	
DB 80P 6m T150S M+	H2	W2	VI4	B	0,3 m	4	725164219_1_r2	B733132	K733239	double sided, one sided pinned, on asphalt	
DB 80P 6m T150S ZDC RR	H2	W2	VI4	B	0,3m	4	725188200_3	B745380	K745380	round recesses	
DB 80P 6m T150S M+ RR	H2	W2	VI4	B	0,3m	4	725188200_3	B714913	K745380	round recesses	
DB 80 NBF											
DB 80 NBF 5m T180 TA P3 M1, M2 and M3	H2	W3	VI1	B	0,2 m	4	725188200_4 725212624_5 725218100_5	B733611	K733611	pinned, variable height (up to 3,5 m)	
DB 80 NBF 5m T180 TA P DBM2	H2	W3	VI1	B	0,2 m	4	725213624_2	B782519-EN.1 B782519-EN.2	K733611	pinned, variable height (up to 3,5 m) Reinforcement DBM2	
DB 100 NBF											
DB 100 NBF 5m T180 SL	H2	W4	VI1	B	0,3 m	4	725109603 rev1	B714756	K714755	free standing, variable height (up to 4,5 m)	
DB 150 NBF											
DB 150 NBF 5m T280	H4b	W5	VI3	B	0,4 m	4	725109603_2	B714757	K732055	free standing, variable height (up to 6,0m)	
Generelle Modifikationen / General Modifications											
Änderung der Bezeichnung der Stahlgüte nach EN 10025-2 / Material designation according to EN 10025-2							725193831_4				
Angabe Betondeckung nach EN 13369:2018 / Indication concrete cover according to EN 13369:2018							725193831_5				
Kupplungen: Anpassung Materialgüte / Couplers: Adaption of material characteristics							725193831_6				
DB 120S-Serie: Trittstufen / Steps							725173254_7				
Anpassung T-Zugband T280E / Adaption T-tension bar T280E							725173254_8				

Munich, 31.03.2023


 Dipl.-Phys. H. Zimmermann
 Deputy Director of the certification body