

CERTIFICATE OF CONSTANCY OF PERFORMANCE

2131/CPR/906

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

MDB L

**ROAD SAFETY STEEL BARRIER FAMILY
LEVEL N2-H1/L1**

Having the performance indicated on page 2 and the any product modifications on the following page (s)

placed on the market under the name or trade mark of

**MEISER Straßenausstattung GmbH
Edmund-Meiser-Straße 3, D-66839 Schmelz-Limbach, GERMANY**

and produced in the manufacturing plant:

**MEISER Straßenausstattung GmbH
Edmund-Meiser-Straße 3, D-66839 Schmelz-Limbach, GERMANY**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1317-5:2007+A2:2012; EN 1317-5:2007+A2:2012/ AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

Constancy of performance of the construction product.

This certificate was first issued on 2020/12/21 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The validity of this Certificate is subject to the regularity of the Surveillance on its FPC.

Issue date: 2020/12/21

Chairman
(Eng. Stefano Calamani)


CERTIFICATE OF CONSTANCY OF PERFORMANCE

2131/CPR/906

MDB L

ROAD SAFETY STEEL BARRIER FAMILY LEVEL N2-H1/L1

placed on the market under the name or trade mark of

MEISER Straßenausstattung GmbH
Edmund-Meiser-Straße 3, D-66839 Schmelz-Limbach, GERMANY

PERFORMANCE UNDER IMPACT

MODEL	CONTAINMENT LEVEL	SEVERITY IMPACT	NORMALISED WORKING WIDTH	NORMALISED DYNAMIC DEFLECTION	NORMALISED VEHICLE INTRUSION
MDB L 4.0	N2	A	W4 (1.2 m)	1.1 m	/
	H1/L1	A	W4 (1.3 m)	1.1 m	VI5 (1.7 m)
MDB L 3.0	N2	A	W3 (1.0 m)	0.9 m	/
	H1/L1	A	W4 (1.2 m)	1.0 m	VI5 (1.7 m)
MDB L 2.0	N2	A	W2 (0.8 m)	0.7 m	/
	H1/L1	A	W3 (1.0 m)	0.8 m	VI5 (1.5 m)

DURABILITY:

RESISTANCE TO SNOW REMOVAL:

DANGEROUS SUBSTANCE:

CONDITIONS FOR USE:

GALVANIZED STEEL IN ACCORDANCE WITH EN ISO 1461

3

NPD

CONFORMITY WITH I.T.T. CONFIGURATION

The test results and the product characteristics are included in the following Test Reports / Relations:

MDB L 4.0

AISICO 2095 (TB42) of 2020/11/24

AISICO 2117 (TB32) of 2020/11/24

MDB L 3.0

AISICO 2098 (TB42) of 2020/11/24

AISICO 2099 (TB32) of 2020/11/24

MDB L 2.0

AISICO 2101 (TB42) of 2020/11/24

AISICO 2102 (TB11) of 2020/11/24

AISICO 2114 (TB32) of 2020/11/24

RI/906 of 2020/12/21

Calculation Report Resistance To Snow Removal of 2020/12/15

Issue date: 2020/12/21

Chairman

(Eng. Stefano Calamani)