



* The coating of the components may vary depending on the durability requirements according to national regulations. The coating type or zinc layer thickness must be specified in the order.

** The post length minimum is 1500mm. If required by national regulations, the post length can be extended up to max. 1900mm. In any case the system height of 750 mm must be observed. If any other length than 1500mm is needed, this must be specified in the order, as well as the coating type or zinc layer thickness.

NO.	PCS	DRAWING NO.	DESCRIPTION	ART. NO.	NO.	PCS	DRAWING NO.	DESCRIPTION	ART. NO.
1	8	A770290	Panhead bolt nose M16x27, 4.6/fl. nut 8	198132	11				
2	2	A770047	Panhead bolt hexagon M16x45, 8.8 / Nut 8	134750	12				
3	2	A770266	Hexagon bolt M16x120, 8.8 / Nut 8	197606	13				
4	2	A770064	F. Plate M16, 115x40x5, RH	154777	14				
5	2	A770057	Washer M16, 30x17.5x3, 100 HV	72152	15				
6	2	A770058	Washer M16, 40x18x4, 200 HV	134760	16				
7	1	A770005	Beam A-01, 3.0mm, 4000mm, UHD85	197873	*	17			
8	2	A770028	Post C100x60x50x4.0/1, 1500mm/UHD140	181199	**	18			
9	2	A770042	Post Stiffer U85x45x4.0, 900mm / UHD140	181200	*	19			
10						20			

<p>SAFETY NOTE! Always use personal safety equipment for installation works. Check all tools and equipment before use!</p>	Date	Name	<p>STD</p>	<p>PROJECT</p>	
	drawn	31.05.2022			LES
	checked	31.05.2022			MAB
approved	31.05.2022	LES	<p>TITLE</p> <p>SAFELINK GG003 Profile A</p>		
4			SC DRAW. NO.	ART. NO.	
3			K770294-NO	198336	
2			REV	SHEET	
1			1 : 48	1	
Changes	Rev.	Name		A3	