



Landesgesellschaft
Österreich

Certificate of constancy of performance Certificate - No.: 0531 – CPR – 1317 – 2890

In compliance with Regulation (EU) No. 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

PRODIGY 7.20s 400

Containment level:	N2
Normalized working width:	W3
Impact severity:	A
Normalized dynamic deflection (m):	0,9
Normalized vehicle intrusion:	NPD
Resistance to snow removal operations:	Class 3
Durability:	Steel, hot dip galvanized, EN ISO 1461

placed on the market by

DELTABLOC INTERNATIONAL GMBH

Kirchdorfer Platz 2
2752 Wöllersdorf, Austria

and produced in the manufacturing plant

ALKA Sanayi Insaat ve Ticaret AS

Cumhuriyet Mah. Erhan Sok. 10
41435 Cayirova, Turkey

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 27.01.2022 based on the assessment report 725193831_3, dated 27.01.2022 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Wien, 27.01.2022

Notified body, No. 0531



(Dipl. – Ing. Gerald Bachler)



Landesgesellschaft
Österreich

**Annex to
certificate of constancy of performance
Certificate - No.: 0531 – CPR – 1317 – 2890**

Construction Product: **PRODIGY 7.20s 400**

Placed on the market by: **DELTABLOC INTERNATIONAL GMBH**
Kirchdorfer Platz 2
2752 Wöllersdorf, Austria

Modification 1: Equivalence of B, A and W profile:
The safety barrier may be installed using guardrails type A, B or W. The assessment of that change was recorded in assessment report 725193831_3.

Approved on 27.01.2022


Modification 2: Equivalence of bolted connection on posts:
The bolted connection between post stiffener and post can be located up to 50 mm downwards. The assessment of that change was recorded in assessment report 725193831_3.

Approved on 27.01.2022

Modification 3: Material of post stiffener:
The post stiffener will be fabricated of material S355JR. The assessment of that change was recorded in assessment report 725193831_3.

Approved on 27.01.2022

Wien, 27.01.2022

Notified body, No. 0531

(Dipl.-Ing. Gerald Bachler)
Notified Body